1 **DIGITAL VIDEO RECORDER FOR ENCRYPTING/DECRYPTING VIDEO**

2 **PROGRAMS IN SEGMENTS TO FACILITATE TRICK PLAY FEATURES**

3

4 **BACKGROUND OF THE INVENTION**

5 **Field of the Invention**

6   The present invention relates to digital video recorders. More particularly, the present

7 invention relates to a digital video recorder for encrypting/decrypting video programs in

8 segments to facilitate trick play features.

9 **Description of the Prior Art**

10   Digital video recorders (DVRs) typically store video programs on a random access

11 storage (RAS) device, such as on a conventional hard disk drive (HDD), which enables certain

12 "trick play" features, such as skipping ahead in a program. The trick play features are enabled by

13 processing frame headers which are recorded in arbitrary length frames of the video program.

14 Due to the arbitrary frame lengths, the video programs are typically processed in unencrypted

15 form in order to detect frame headers which identify frame boundaries. Thus, prior art DVRs

16 typically store copyrighted video programs in unencrypted form so that the DVR can randomly

17 access individual frames during playback. This design, however, subjects the copyrighted

18 material to unauthorized reproduction, for example, by eavesdropping while the copyrighted

19 content is transferred from the DVR host circuitry to the RAS device.

20   Prior art DVRs typically employ a conventional hard disk drive (HDD), such as an IDE

21 hard disk drive, as the RAS device since HDDs have sufficient capacity to store video content

22 and are relatively inexpensive due to their prevalent use in personal computers (PCs). Rather

23 than design and manufacture a customized HDD for the DVR market, DVRs are constructed

24 similar to a PC, including DVR host circuitry for interfacing with a commodity HDD which

25 reduces the cost of the DVR. Using a conventional HDD, however, has rendered the DVR more

26 susceptible to unauthorized copying of video programs since the HDD can be removed and

27 installed in another DVR or in a PC.

1   There is, therefore, a need to protect against unauthorized reproduction of copyrighted

2   video programs in a DVR employing a cost effective, commodity HDD, while supporting trick

3   play features.

4   **SUMMARY OF THE INVENTION**

5   The present invention may be regarded as a digital video recorder (DVR) for storing a

6   plaintext video program as an encrypted video program. The DVR comprises a random access

7   storage (RAS) device for storing the encrypted video program in encrypted segments. The DVR

8   further comprises a cryptography facility comprising an encoder for encrypting plaintext

9   segments of the plaintext video program into the encrypted segments stored on the RAS device,

10   and a decoder for randomly and independently decrypting the encrypted segments of the

11   encrypted video program into plaintext segments during playback.

12   In one embodiment the cryptography facility comprises a pseudo-random sequence

13   generator for generating a pseudo-random sequence. In one embodiment, the pseudo-random

14   sequence generator is initialized with segment seed values corresponding to the plaintext

15   segments of the plaintext video program , and the encoder combines the pseudo-random

16   sequence generated for each segment seed value with the plaintext segments of the plaintext

17   video program to generate the encrypted segments of the encrypted video program stored on the

18   RAS device. During playback, the pseudo-random sequence generator is initialized with

19   segment seed values corresponding to the encrypted segments of the encrypted video program,

20   and the decoder combines the pseudo-random sequence generated for each segment seed value

21   with the encrypted segments of the encrypted video program to generate the plaintext segments

22   of the plaintext video program.

23   In an alternative embodiment, the RAS device comprises a hard disk drive (HDD)

24   comprising a disk, the disk comprises a plurality of data tracks, each track comprises a plurality

25   of data sectors, and each data sector stores an encrypted segment of the encrypted video program.

26   The present invention may also be regarded as a method for processing a video program

27   in a digital video recorder comprising a random access storage (RAS) device. Plaintext segments

1   of a plaintext video program are encrypted into encrypted segments. The encrypted segments are

2   stored on the RAS device and, during playback, randomly read from the RAS device. Each

3   encrypted segment is then independently decrypted into a plaintext segment.

4   **BRIEF DESCRIPTION OF THE DRAWINGS**

5   FIG. 1 shows a digital video recorder according to an embodiment of the present

6   invention wherein a video program is encrypted in segments, and the encrypted segments stored

7   on a random access storage device.

8   FIG. 2 shows a digital video recorder according to an alternative embodiment of the

9   present invention wherein video programs are stored in encrypted form on a hard disk drive

10   (HDD) using plaintext keys which are also encrypted using a pseudo-random sequence generated

11   from a unique ID and stored in encrypted file system entries on the HDD.

12   FIG. 3A shows a programmable file system (FS) polynomial implemented using a linear

13   feedback shift register (LFSR) for generating the pseudo-random sequence of FIG. 2, wherein a

14   seed value is generated for the LFSR from the unique ID.

15   FIG. 3B shows a programmable FS polynomial implemented using a LFSR for

16   generating the pseudo-random sequence of FIG. 2, wherein coefficient values are generated for

17   the LFSR from the unique ID.

18   FIG. 4A shows an LFSR for generating a pseudo-random sequence for encrypting a

19   plaintext video program using a plaintext key as a seed value for the LFSR.

20   FIG. 4B shows an LFSR for generating a pseudo-random sequence for encrypting a

21   plaintext video program using a plaintext key, wherein a seed value is generated from the

22   plaintext key. In an alternative embodiment, a plurality of segment seed values are generated

23   from the plaintext key wherein each segment seed value is used to encrypt a corresponding

24   segment of the plaintext video program.

25   FIG. 4C shows an LFSR for generating a pseudo-random sequence for encrypting a

26   plaintext video program using a plaintext key, wherein coefficient values are generated from the

27   plaintext key. In an alternative embodiment, sets of coefficient values are generated from the

SCANNED, # 12

1   plaintext key wherein each set of coefficient values is used to encrypt a corresponding segment

2   of the plaintext video program.

3   **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

4   FIG. 1 shows a digital video recorder (DVR) 1 for storing a plaintext video program as an

5   encrypted video program according to an embodiment of the present invention. The DVR 1

6   comprises a random access storage (RAS) device 3 for storing the encrypted video program in

7   encrypted segments 5. The DVR 1 further comprises a cryptography facility 14 comprising an

8   encoder 24 for encrypting plaintext segments 7A of the plaintext video program into the

9   encrypted segments 5 stored on the RAS device 3, and a decoder 26 for randomly and

10   independently decrypting the encrypted segments 5 of the encrypted video program into plaintext

11   segments 7B during playback.

12   The DVR 1 of FIG. 1 further comprises a video controller 28 for receiving video data 30

13   from an external entity (e.g., a cable or satellite) and for providing video data 34 to a display

14   device during playback. The video controller 28 processes the headers in the video frames of the

15   video data 30 in order to implement trick play features. Certain trick play features, such as skip

16   ahead or behind, require that the video program be accessed randomly rather than in a

17   consecutive sequence of frames. The DVR 1 of FIG. 1 facilitates this feature by decrypting the

18   video program in segments. When the video controller 28 requires access to a particular segment

19   of the video program, it initializes the decoder 26 with an appropriate segment key for decrypting

20   the video segment as it is read from the RAS device 3.

21   FIG. 2 shows a DVR 2 according to an embodiment of the present invention wherein the

22   RAS device 3 of FIG. 1 is implemented as a hard disk drive (HDD) 6. The HDD 6 stores a

23   plurality of encrypted video programs 8 and an encrypted file system, the encrypted file system

24   comprising a plurality of encrypted file system entries 10 for decrypting the plurality of

25   encrypted video programs 8. The DVR 2 further comprises host circuitry 12 for interfacing with

26   the HDD 6, the host circuitry 12 comprising the cryptography facility 14 for encrypting plaintext

27   file system entries 16A into the encrypted file system entries 10 stored on the HDD 6, and for

1   decrypting the encrypted file system entries 10 read from the HDD 6 into plaintext file system

2   entries 16B. The cryptography facility 14 comprises a pseudo-random sequence generator 20,

3   responsive to the unique ID 4, for generating a pseudo-random sequence 22. The cryptography

4   facility 14 further comprises an encoder 24 for combining the pseudo-random sequence 22 with

5   the plaintext file system entries 16A to generate the encrypted file system entries 10 stored on the

6   HDD 6, and a decoder 26 for combining the pseudo-random sequence 22 with the encrypted file

7   system entries 10 read from the HDD 6 to generate the plaintext file system entries 16B.

8   In one embodiment, the encoder 24 of FIG. 2 performs the encryption operation by

9   XORing each element (e.g., byte) of the plaintext file system entry 16A with a corresponding

10   element (e.g., byte) of the pseudo-random sequence 22. Similarly, the decoder 26 performs the

11   decryption operation by XORing each element (e.g., byte) of the encrypted file system entry 10

12   with a corresponding element (e.g., byte) of the pseudo-random sequence 22 to generate the

13   plaintext file system entry 16B.

14   The video controller 28 generates control signals 32 for controlling the operation of the

15   cryptography facility 14 when recording an encrypted video program 8, together with the

16   encrypted file system entry 10 for decrypting the encrypted video program 8. The video

17   controller also processes the decrypted file system entries 16B so that the encrypted video

18   programs 8 can be decrypted and output as video data 34 to a display device. Because the file

19   system entries 10 are stored in encrypted form relative to the unique ID 4 assigned to the DVR 2,

20   the encrypted video programs 8 stored on the HDD 6 cannot be decrypted by connecting the

21   HDD 6 to another DVR or to a PC. In effect, the HDD 6 is married to the host circuitry 12 of the

22   DVR 2 through the unique ID 4 which protects against unauthorized copying. In addition, the

23   encrypted file system entries 10 are transparent to the operation of the HDD 6 so that any

24   conventional HDD 6 may be employed without modification.

25   In one embodiment, the plaintext file system entry 16A comprises a plaintext key for

26   encrypting a plaintext video program into an encrypted video program 8 stored on the HDD 6.

27   The cryptography facility 14 encrypts the plaintext video program into an encrypted video

1   program 8 stored on the HDD 6, and encrypts the plaintext key into an encrypted key stored on

2   the HDD 6 in an encrypted file system entry 10. In one embodiment, the encoder 24 combines

3   the pseudo-random sequence 22 with the plaintext video program to generate the encrypted video

4   program 8 stored on the HDD 6.

5   In another embodiment, the encrypted file system entry 10 comprises an encrypted key

6   for decrypting an encrypted video program 8 read from the HDD 6 into a plaintext video

7   program. The cryptography facility 14 decrypts the encrypted key read from encrypted file

8   system entry 10 into a plaintext key, and decrypts the encrypted video program 8 read from the

9   HDD 6 using the plaintext key. In one embodiment, the decoder 26 combines the pseudo-

10   random sequence 22 with the encrypted video program 8 read from the HDD 6 to generate the

11   plaintext video program.

12   In one embodiment, the pseudo-random sequence generator 20 comprises a

13   programmable file system (FS) polynomial for generating the pseudo-random sequence 22. In

14   one embodiment, the programmable FS polynomial is programmed with coefficients which, in

15   one embodiment, are generated by a coefficient generator responsive to the unique ID 4. In

16   another embodiment, the programmable FS polynomial is programmed with a seed value which,

17   in one embodiment, is generated by a seed value generator responsive to the unique ID 4.

18   FIG. 3A shows an embodiment of the present invention wherein the FS polynomial is

19   implemented using a suitable linear feedback register (LFSR) 36. An LFSR may be

20   implemented using a number of different configurations. The LFSR 36 of FIG. 3A comprises a

21   shift register 38 comprising N storage elements which are initialized with a seed value 40

22   generated by a seed value generator 50 from the unique ID 4. A number of taps 42A-42E

23   connect a corresponding number of the storage elements to an adder 44 for adding the values

24   stored in the storage elements. The resulting sum 44 is fed back 46 to an input of the LFSR 36.

25   The LFSR 36 is shifted from left to right, and the right most storage element 48 outputs each

26   value of the pseudo-random sequence 22.

27   FIG. 3B shows an alternative embodiment of the present invention wherein the FS

1 polynomial is implemented using an LFSR 52 comprising programmable coefficients 54_0-54_N. A

2 coefficient generator 56 generates coefficient values 58 for programming each of the

3 programmable coefficients 54_0-54_N. In the embodiment shown in FIG. 3B, the coefficients are

4 binary valued and the programmable coefficients 54_0-54_N are implemented as switches.

5 In yet another embodiment of the present invention, the FS polynomial is implemented

6 using an LFSR comprising both a programmable seed value and programmable coefficients

7 values which are generated from the unique ID 4.

8 In one embodiment, the seed value generator 50 implements a function f(x), such as a

9 polynomial, with the unique ID 4 as the input argument x and the seed value 40 the result. In

10 another embodiment, the seed value generator 50 comprises a programmable algorithm for

11 computing the seed value 40 from the unique ID 4. This embodiment allows a DVR

12 manufacture to select the function f(x) for implementing a line of DVRs. This embodiment also

13 allows an external entity to update the programmable algorithm to protect against system

14 compromise. For example, in one embodiment the DVR 2 of FIG. 2 comprises network circuitry

15 for connecting to a network (e.g., through a cable or satellite), and a system administrator on the

16 network periodically changes the programmable algorithm in a random manner. Thus, if an

17 attacker discovers the algorithm used by the seed value generator 50 to generate the seed value

18 40, the compromise is only temporary until the system administrator updates the algorithm.

19 In another embodiment, the coefficient value generator 56 implements a plurality of

20 functions f(x), such as a plurality of polynomials, with the unique ID as the input argument x and

21 the coefficient values 58 the result of each function f(x). The coefficient value generator 56 may

22 also implement a programmable algorithm for computing the coefficient values 58 to facilitate

23 different DVR manufactures and to protect against system compromise as described above.

24 In another embodiment of the present invention, the seed value generator 50 comprises a

25 seed table comprising a plurality of table entries, each table entry comprising a seed value. An

26 index generator, responsive to the unique ID 4, generates an index into the seed table. In yet

27 another embodiment, the coefficient value generator 56 comprises a coefficient table comprising

1   a plurality of table entries, each table entry comprising coefficient values. An index generator,

2   responsive to the unique ID 4, generates an index into the coefficient table.

3   FIG. 4A shows an alternative embodiment of the present invention as comprising a

4   programmable LFSR 59 for generating a pseudo-random sequence 22 used to encrypt a plaintext

5   video program into an encrypted video program 8 stored on the HDD 6. A plaintext key 18 is

6   used as a seed value for the LFSR 59, where the plaintext key 18 is associated with the plaintext

7   video program. In one embodiment, the plaintext key is derived from the filename or other

8   attribute of the video program. In another embodiment, the plaintext key is generated randomly

9   using any suitable method, for example, by reading a system clock value just prior to encrypting

10   the plaintext video.

11   FIG. 4B shows an alternative embodiment of the present invention as comprising a

12   programmable LFSR 60 for generating a pseudo-random sequence 22 used to encrypt a plaintext

13   video program into an encrypted video program 8 stored on the HDD 6. A seed value generator

14   62 generates a seed value 64 used to initialize the shift register 38. The seed value 64 is

15   generated from the plaintext key 18 used to encrypt the plaintext video program. In one

16   embodiment, the plaintext video program is encrypted in segments, and the seed value generator

17   62 generates a distinct seed value 64 for each segment number 66. Each segment seed value 64

18   is essentially a distinct key for use in encrypting a corresponding segment of the plaintext video

19   program. In this manner, compromise of a single key enables successful decrypting of only a

20   segment of the encrypted video program. Further, encrypting the video program in segments

21   facilitates trick play features during playback as described above.

22   In one embodiment, the plaintext key 18 comprises a plurality of segment keys for

23   encrypting each segment of the plaintext video program, and the seed value generator 62

24   generates a corresponding seed value 64 for each segment key. In another embodiment, the

25   segment keys are computed from the plaintext key 18, and the seed value generator 62 generates

26   a corresponding seed value 64 for each computed segment key. In one embodiment, the seed

27   value generator 62 comprises a function f(x,y) for computing the segment seed values 64 wherein

1   the plaintext key 18 and segment number 66 are the input arguments x and y, and the segment

2   seed value 64 is the result. Lookup tables may also be employed for generating the segment

3   keys, and the algorithm for computing the segment keys may be programmably updated to

4   facilitate different DVR manufactures and to protect against system compromise as described

5   above.

6   FIG. 4C shows an alternative embodiment of the present invention as comprising a

7   programmable LFSR 68 for generating a pseudo-random sequence 22 used to encode a plaintext

8   video program into an encrypted video program 8 stored on the HDD 6. A coefficient value

9   generator 70 generates a coefficient values 72 used to initialize the coefficients of the LFSR 68.

10   The coefficient values 72 are generated from the plaintext key 18 used to encrypt the plaintext

11   video program. In one embodiment, the plaintext video program is encrypted in segments, and

12   the coefficient value generator 70 generates distinct coefficient values 72 for each segment

13   number 66. Similar to the embodiment of FIG. 4B, each set of coefficient values 72 is

14   essentially a distinct key for use in encrypting a corresponding segment of the plaintext video

15   program so that compromise of a single key enables successful decrypting of only a segment of

16   the encrypted video program. Further, decrypting the video program in segments facilitates trick

17   play features during playback as described above.

18   In one embodiment, the plaintext key 18 comprises a plurality of segment keys for

19   encrypting each segment of the plaintext video program, and the coefficient value generator 70

20   generates a set of coefficient values 72 for each segment key. In another embodiment, the

21   segment keys are computed from the plaintext key 18, and the coefficient value generator 70

22   generates a corresponding set of coefficient values 72 for each computed segment key. In one

23   embodiment, the coefficient value generator 70 comprises a function $f(x,y)$ for computing the

24   segment coefficient values 72 wherein the plaintext key 18 and segment number 66 are the input

25   arguments x and y, and the segment coefficient values 72 are the result. Lookup tables may also

26   be employed for generating the segment keys, and the algorithm for computing the segment keys

27   may be programmably updated to facilitate different DVR manufactures and to protect against

1 system compromise as described above.

2 In another embodiment, the LFSR 60 of FIG. 4B or the LFSR 68 of FIG. 4C is used to

3 decrypt an encrypted video program 8 in segments using the segment keys. In one embodiment,

4 the plaintext key 18 comprises a plurality of segment keys which are encrypted and stored as an

5 encrypted file system entry 10 for use in decrypting the encrypted video program 8 during

6 playback. In another embodiment, the plaintext key 18 is encrypted and stored as an encrypted

7 file system entry 10. During playback, the encrypted key is decrypted into the plaintext key 18,

8 and the plaintext key 18 is used to generate the segment keys for use in decrypting the encrypted

9 video program 8 in segments.

10 In one embodiment, the HDD 6 comprises a disk having a plurality of data tracks, where

11 each data track comprises a plurality of data sectors. In the embodiments of FIG. 4B and 4C, a

12 segment of a video program corresponds to a data sector. This simplifies the design since data is

13 typically written to and read from a conventional HDD 6 in sector blocks. In one embodiment,

14 the encrypted key for use in decrypting a corresponding sector is stored in the sector.

15 In another embodiment of the present invention, the unique ID 4 is implemented using

16 tamper and inspection resistant circuitry to protect against discovery. In one embodiment, the

17 host circuitry 12 and unique ID 4 are implemented within an integrated circuit (IC), and the

18 unique ID 4 is buried, scattered or otherwise concealed within the IC using any suitable method.

19 In yet another embodiment, at least part of the cryptography facility 14 (e.g., the seed value

20 generator 62 of FIG. 4B or the coefficient value generator 70 of FIG. 4C) is implemented using

21 tamper and inspection resistant circuitry to protect against discovery. An example of tamper and

22 inspection resistant circuitry is disclosed in Tygar, J.D. and Yee, B.S., "Secure Coprocessors in

23 Electronic Commerce Applications," Proceedings 1995 USENIX Electronic Commerce

24 Workshop, 1995, New York, which is incorporated herein by reference.

25 The embodiments of the present invention may be implemented in circuitry or software

26 or both. The circuitry and/or software may be static or field programmable as described above.

27 Software embodiments comprise code segments embodied on a computer readable medium, such

1 as a hard disk, floppy disk, compact disk (CD), digital video disk (DVD), or programmable

2 memory (e.g., an EEPROM). The code segments may be embodied on the computer readable

3 medium in any suitable form, such as source code segments, assembly code segments, or

4 executable code segments.